(19) World Intellectual Property Organization International Bureau

PO OMPI



(43) International Publication Date 17 February 2005 (17.02.2005)

PCT

(10) International Publication Number WO 2005/014292 A3

(51) International Patent Classification7: B41J 2/14, 2/16

(21) International Application Number:

PCT/GB2004/003109

(22) International Filing Date: 19 July 2004 (19.07.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0316934.9

19 July 2003 (19.07.2003) GB

(71) Applicant (for all designated States except US): XAAR TECHNOLOGY LIMITED [GB/GB]; Science Park, Cambridge CB4 OXR (GB).

- (72) Inventor; and
- (75) Inventor/Applicant (for US only): DRURY, Paul, Raymond [GB/GB]; 8 New Road, Great Chishill, Royston, Hertfordshire SG8 8ST (GB).
- (74) Agents: GARRATT, Peter, Douglas et al.; Mathys & Squire, 120 Holborn, London EC1N 2SQ (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

- with international search report

(88) Date of publication of the international search report: 7 April 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF MANUFACTURING A COMPONENT FOR DROPLET DEPOSITION APPARATUS



(57) Abstract: A nozzle plate component is manufactured by forming a layer of photoresist on a substrate and selectively exposing and removing material to define an array of distinct bodies. Nickel is then electroformed around the bodies to form a plate, with nozzles subsequently formed by ablation through the photoresist. The process can essentially be repeated to form a guard structure around each nozzle.



